

# Troubleshooting

● Before sending the equipment for repair, inspect the equipment as follows.

Symptom	Items to be inspected	How to repair
Power is not supplied	<ul style="list-style-type: none"><li>● Is power plug correctly inserted into socket?</li><li>● Is OFF timer actuated? Is power switch OFF?</li></ul>	<ul style="list-style-type: none"><li>➔ Correctly insert power plug into socket.</li><li>➔ Turn "ON" power ON/OFF switch.</li></ul>
Large "sputtering"	<ul style="list-style-type: none"><li>● Is pre-filter clogged?</li></ul>	<ul style="list-style-type: none"><li>➔ This is not a failure. Clean up pre-filter. (See P6.)</li></ul>
Air blown weakly	<ul style="list-style-type: none"><li>● Is pre-filter clogged?</li></ul>	<ul style="list-style-type: none"><li>➔ Clean up pre-filter. (See P6.)</li></ul>

■ If the symptom remains even after the above inspections, immediately turn "OFF" the power ON/OFF switch to prevent accident, be sure to remove the power plug from the socket, and request that your distributor inspect and repair the equipment.

\*Never attempt to repair the equipment yourself because it is very dangerous.

## Recommendation for maintenance contract

To maintain an effective deodorizing effect over the long term, the optical catalyst unit should be maintained semi annually, and the dust collection unit every month or two. Consult your distributor for conclusion of a maintenance contract.